



DIMENSIONS & POWER	
Form Factor	Desktop / Wall Mounted
Dimensions (H x W x D)	34 x 131 x 180 mm (1.34 x 5.16 x 7.09 in)
Rack Mountable	Yes (Optional)
DIN-rail Mountable	Yes (Optional)
Maximum Power Consumption	9.2 Watt
Power Supply (AC)	100-240 VAC, 50-60 Hz
Power Supply (DC)	-
Redundant Power Supplies	-
Hot-swappable Power Supplies	-

INTERFACES & MODULES	
Ethernet Interfaces	4 x 1 GbE RJ45
Power-over-Ethernet Interfaces	-
Ethernet Bypass Interfaces	-
Console Port	1 x COM RJ45
Number of Expansion Slots	-

OPERATING ENVIRONMENT & CERTIFICATIONS	
Safety	CE, UL
EMC	FCC, CE, VCCI
Operating & Storage Humidity	0 % to 95 % (Non-condensing)
Operating Temperature	5°C to 35°C (41°F to 95°F)

SYSTEM PERFORMANCE & CAPACITY	NETWALL 110	NETWALL 140
Firewall Throughput ¹ (1518 / 512 / 64 byte, UDP)	1 / 1 / 0.38 Gbps	4 / 3 / 0.38 Gbps
Firewall Throughput ¹ (Packets per Second)	742 Kpps	742 Kpps
Concurrent Connections	128,000	256,000
New Connections/Second (TCP)	42,000	42,000
IPsec VPN Throughput ² (1420 / 512 / 64 byte, UDP)	100 / 100 / 73 Mbps	250 / 250 / 73 Mbps
IPsec VPN Throughput ² (Software Only) (1420 / 512 / 64 byte, UDP)	-	-
Gateway-to-Gateway or Roaming IPsec VPN Tunnels	50	100
OneConnect VPN Throughput (TCP)	100 Mbps	250 Mbps
OneConnect VPN Tunnels	50	100
VLANs	128	128
Virtual Routers	10	20

